

---

*North America's Leader in Hazardous Material Information Management*  
*1905 Aston Avenue, Carlsbad, CA 92008*  
*Phone (800) 451-8346 Fax (760) 602-8888*

---

## MSDS PRODUCT INFORMATION

Date: 10/07/2005  
To: MSDS Requester  
From: 3E Company  
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☒ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Sherwin-Williams Company  
Product Name: Ralph Lauren Interior Matte Wall Finish, Polo Mallet White (DISCONTINUED)

# MATERIAL SAFETY DATA SHEET

RL1190-  
04 00

MANUFACTURER'S NAME  
Manufactured for:  
POLO RALPH LAUREN L.P.  
New York, NY 10022

EMERGENCY TELEPHONE NO.  
(216) 566-2917

DATE OF PREPARATION  
18-MAR-98

INFORMATION TELEPHONE NO.  
(216) 566-2902

## Section I -- PRODUCT IDENTIFICATION

PRODUCT NUMBER	RL1190-	HMIS CODES	
		Health	2*
		Flammability	0
		Reactivity	0

PRODUCT NAME  
RALPH LAUREN\* Interior Matte Wall Finish, Polo Mallet White  
PRODUCT CLASS  
Latex Paint

## Section II -- HAZARDOUS INGREDIENTS

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Ethylene Glycol. 107-21-1	5 C	50	50	PPM	0.12
Cristobalite 14464-46-1	0.1	0.05	0.05	MG/M3 as Resp. Dust	
Calcium Carbonate. 471-34-1	3	10	15(5)	MG/M3 as Dust ***	
		*** Total Dust (Respirable Fraction)			
Titanium Dioxide. 13463-67-7	16	10	10(5)	MG/M3 as Dust ***	
		*** Total Dust (Respirable Fraction)			
pH ~ 9.0					

## Section III -- PHYSICAL DATA

PRODUCT WEIGHT -- 11.39 lb./gal. EVAPORATION RATE -- Slower than Ether  
SPECIFIC GRAVITY -- 1.37 VAPOR DENSITY -- Heavier than Air  
BOILING POINT -- 212-477 F MELTING POINT -- N.A.  
VOLATILE VOLUME -- 59 % SOLUBILITY IN WATER -- N.A.  
VOC (Theoretical) -- 1.62 lb. 194 gm. (less Federally Exempt Solvents)

## Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	LEL	UEL
Not Applicable	N.A.	N.A.

FLAMMABILITY CLASSIFICATION  
Not Applicable

EXTINGUISHING MEDIA  
Carbon Dioxide, Dry Chemical, Alcohol Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

Continued on page 2

## =====

**SPECIAL FIRE FIGHTING PROCEDURES**  
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## =====

**Section V -- HEALTH HAZARD DATA**

## -----

**ROUTES OF EXPOSURE**

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

**ACUTE Health Hazards**

**EFFECTS OF OVEREXPOSURE**

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

None generally recognized.

**EMERGENCY AND FIRST AID PROCEDURES**

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Get medical attention.

**CHRONIC Health Hazards**

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m<sup>3</sup> developed lung cancer, however, such exposure levels are not attainable in the workplace.

## =====

**Section VI -- REACTIVITY DATA**

**STABILITY --** Stable

**CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

Continued on page 3

---

Section VII -- SPILL OR LEAK PROCEDURES

---

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

## WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

---

Section VIII -- PROTECTION INFORMATION

---

## PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m<sup>3</sup> (total dust), 3 mg./m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg./m<sup>3</sup> (total dust), 5 mg./m<sup>3</sup> (respirable fraction).

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

---

Section IX -- PRECAUTIONS

---

## DOL STORAGE CATEGORY

Not Applicable

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

---

Section X -- OTHER REGULATORY INFORMATION

---

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

---

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol.	5	

---

Continued on page 4

## =====

## CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

## TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.